

# JABRA EVOLVE 30/40

## MORE THAN HEADSETS, A WORKPLACE EVOLUTION

- Made for voice calls and music
- Passive noise cancellation
- USB and 3.5mm connectivity to laptop and smart device
- Integrated busy light on ear cups (Evolve 40)



DETAIL	INFORMATION JABRA EVOLVE 30	INFORMATION JABRA EVOLVE 40
Packaging dimensions	L 23 x W 18 x H 3.5 cm	L 19.0 x W 25.5 x H 1.0 cm
Weight mono / duo	Mono headset 171.1 g Stereo headset 142.5 g	Mono headset 171.1 g Stereo headset 142.5 g
What is in the box	Jabra Evolve 30 headset, pouch, warning leaflet, warranty leaflet, quick start guide, foam inlay (only available for duo), layer card, poly bag	Jabra Evolve 40 headset, pouch, warning leaflet, warranty leaflet, quick start guide, foam inlay (only available for duo), layer card, poly bag
Battery included	N/A	N/A
AC power supply	USB power supply by PC	USB power supply by PC
Certifications	Regulatory Approvals: CE, FCC, KCC, RCM, UL Industrial Certifications: Skype for Business, Lync, Avaya, Cisco	Regulatory Approvals: CE, FCC, KCC, RCM, UL Industrial Certifications: Skype for Business, Lync, Avaya, Cisco, Alcatel Lucent and Aastra
Warranty	2 years	2 years
Bluetooth device	No	No
DECT device	No	No
NFC	No	No
Headset bandwidth	Wideband	Wideband
Connection (mini jack, USB, etc.)	USB, 3.5mm jack	USB 2.0/3.0, 3.5mm jack
Speaker size	D28x3.9mm	D28x3.9mm
Speaker sensitivity	93.6dB SPL @ 1kHz	93.6dB SPL @ 1kHz
Speaker impedance	32+/-4.8Ω, @ 1.0kHz	32+/-4.8Ω, @ 1.0kHz
Speaker max input power	Rated Input 5mW @ 0.4V, max input 10mW @ 0.56V	Rated Input 5mW @ 0.4V, max input 10mW @ 0.56V
Speaker frequency range	150Hz~7kHz, @ Output S.P.L -10dB	150Hz~7kHz, @ Output S.P.L -10dB
Microphone type	Electret condenser (ECM)	Electret condenser (ECM) Uni-Directional Microphone
Microphone sensitivity	F=1kHz, pin=1Pa, 0dB=1V/Pa, Min=-48dB, Max=-44dB	F=1kHz, pin=1Pa, 0dB=1V/Pa. Min: -42 dB, Max: -38 dB
Microphone frequency range	100Hz ~ 10kHz @ 6dB Jabra	100 Hz - 10 kHz
Speaker bandwidth music mode	Wideband	HiFi
Speaker bandwidth speak mode	Wideband	Wideband
Microphone bandwidth	Wideband	Wideband
Cord length	Control cable: 95cm, HS cable: 120cm	Control cable: 95cm, HS cable: 120cm
Operating temperature	-10 °C to + 50 °C	-10 °C to + 50 °C
Storage temperature	-30°C to + 80°C Storage temperature range: (-20°C to +35°C 6 months), (+35°C to +45°C 3 months), (+45°C to +45°C 1 month), (+60°C to +70°C 1 hour with no degradation), (+70°C to +85°C max. 1 hour < 20% degradation)	-30°C to + 80°C Storage temperature range: (-20°C to +35°C 6 months), (+35°C to +45°C 3 months), (+45°C to +45°C 1 month), (+60°C to +70°C 1 hour with no degradation), (+70°C to +85°C max. 1 hour < 20% degradation)
Power consumption speaker	Rated Input 5mW @ 0.4V, max input 10mW @ 0.56V	Rated Input 5mW @ 0.4V, max input 10mW @ 0.56V
Features*	HD voice, PeakStop™ technology, UC Plug-and-play, noise canceling microphone, HiFi sound, easy call management, Jabra software applications, crystal clear sound, around the ear wearing style, passive noise cancellation, connects to multiple devices (smartphone or tablet) with a 3.5mm jack	HD voice, PeakStop™ technology, UC Plug-and-play, noise canceling microphone, HiFi sound, easy call management, Jabra software applications, crystal clear sound, around the ear wearing style, passive noise cancellation, integrated busy light, discreet boom arm with magnet that clicks onto the headband when not in use / not needed, Jabra Intelligent Call Transfer that allows the transfer of calls from Skype for Business to your smartphone using the 3.5mm jack.

SKU	DESCRIPTION	EAN CODE
5399-823-309	Jabra Evolve 30 II MS Stereo	5706991019964
5399-829-309	Jabra Evolve 30 II UC Stereo	5706991019971
5393-823-309	Jabra Evolve 30 II MS Mono	5706991019940
5393-829-309	Jabra Evolve 30 II UC Mono	5706991019957
6399-823-109	Jabra Evolve 40 MS Stereo	5706991017014
6399-829-209	Jabra Evolve 40 UC Stereo	5706991017021
6393-823-109	Jabra Evolve 40 MS Mono	5706991017038
6393-829-209	Jabra Evolve 40 UC Mono	5706991017045

\* Phone dependent